NSN 5925-01-102-6485

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-102-6485 **Body Style:** Single pole type **Body Length:** 2.000 inches **Body Width:** 0.750 inches **Case Material:** Plastic **Center To Center Distance Between Terminals Parallel To Length:** 1.530 inches **Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:** 1.660 inches **Boss Height:** 0.130 inches **Mounting Surface To Terminal End Distance:** 2.032 inches **Pole Quantity: Mounting Facility Type And Quantity:** 2 threaded hole Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 **Maximum Continuous Load Current Rating Per Pole:** 5.0 amperes ac single location Operating Voltage Type And Rating Per Pole In Volts: 250.0 ac single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 1000.0 ac single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Magnetic-hydraulic single location **Trip Release Characteristic:** Instantaneous single location **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 single location **Reset Method:**

Manual

Main Contact Tripping Mechanism Type:

Trip free

NSN 5925-01-102-6485 Circuit Breaker - Page 2 of 2



Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole one
Internal Trip Release Configuration:
Relay trip single location
Thread Size:
0.138 inches
Inclosure Protection Type For Which Designed:
Fungus resistant and moisture resistant
Frequency In Hertz:
50.0 single location or 60.0 single location
Thread Series Designator:
Unc
Terminal Type And Quantity:
4 tab w/screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0