

View Online at <https://aerobasegroup.com/nsn/5925-01-102-6486>

**Body Style:**

Multipole-single actuator type

**Bushing Length:**

0.250 inches

**Body Length:**

1.300 inches

**Body Width:**

2.063 inches

**Body Height:**

1.875 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

0.750 inches

**Center To Center Distance Between Terminals Parallel To Width:**

0.688 inches

**Pole Quantity:**

3

**Mounting Facility Type And Quantity:**

1 threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

1.5 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

120.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

300.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Thermal all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

138.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 push-pull

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole two

**Internal Trip Release Configuration:**

Series trip all locations

**Thread Size:**

0.469 inches

**Trip Delay Time In Seconds Per Rated Continuous Current:**

0.100 at 400 pct all locations and 0.700 at 400 pct all locations

**Inclosure Protection Type For Which Designed:**

Fungus resistant

**Trip Release Ambient Temperature Rating:**

65.0 degrees celsius all locations

**Frequency In Hertz:**

400.0 all locations

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

6 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0