## NSN 5925-01-104-3445



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-01-104-3445 **Body Style:** Multipole-multiple actuator type **Body Length:** 3.344 inches **Body Width:** 2.000 inches **Body Height:** 2.812 inches **Case Material: Plastic Center To Center Distance Between Terminals Parallel To Width:** 1.000 inches **Boss Height:** 0.250 inches **Pole Quantity: Mounting Facility Type And Quantity:** 4 terminal Storage Type: General purpose warehouse **Maximum Continuous Load Current Rating Per Pole:** 15.0 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:** 240.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 10000.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Thermal-magnetic all locations **Trip Release Characteristic:** Instantaneous all locations and time delay all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 all locations **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free **Manual Actuator Type And Quantity:** 2 toggle

**Actuator Function:** Trip-reset

## **NSN 5925-01-104-3445** Circuit Breaker - Page 2 of 2



Actuator Position Designation:
At each pole
External Actuator Linkage Arrangement:
One and two linked
Trip Delay Time In Seconds Per Rated Continuous Current:
120.000 at 200 pct all locations
Inclosure Protection Type For Which Designed:
Fungus resistant and moisture resistant
Trip Release Ambient Tempurature Rating:
40.0 degrees celsius all locations
Frequency In Hertz:
60.0 all locations
Test Data Document:
81348-w-c-375 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
2 compression and 2 quick disconnect, male
Specification Data:
81348-w-c-375/14 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0