

View Online at <https://aerobasegroup.com/nsn/5925-01-104-7348>

**Body Style:**

Multipole-multiple actuator type

**Body Length:**

2.500 inches

**Body Width:**

3.060 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

1.955 inches

**Center To Center Distance Between Terminals Parallel To Width:**

0.760 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

2.070 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.760 inches

**Boss Height:**

0.165 inches

**Mounting Surface To Terminal End Distance:**

2.491 inches

**Pole Quantity:**

4

**Mounting Facility Type And Quantity:**

8 threaded hole

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

50.0 amperes ac first location

**Operating Voltage Type And Rating Per Pole In Volts:**

250.0 ac third location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

1000.0 ac third location

**Circuit Protection Type:**

Overcurrent third location

**Trip Release Method:**

Magnetic third location

**Trip Release Characteristic:**

Time delay first location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 third location

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

4 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At each pole

**External Actuator Linkage Arrangement:**

One, two, three, and four linked

**Internal Trip Release Configuration:**

Series trip third location

**Thread Size:**

0.138 inches

**Trip Delay Time In Seconds Per Rated Continuous Current:**

2.000 at 200 pct third location and 12.000 at 200 pct third location

**Inclosure Protection Type For Which Designed:**

Explosion proof and fungus resistant and moisture resistant

**Special Features:**

Pole 4 shall be a dummy pole

**Frequency In Hertz:**

400.0 third location

**Test Data Document:**

18876--55629-002 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

8 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0