NSN 5925-01-105-0549

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-105-0549

Body Style:

Multipole-single actuator type

Bushing Length:

0.380 inches

Body Length:

1.500 inches

Body Width:

1.250 inches

Case Material:

Metal

Center To Center Distance Between Terminals Parallel To Length:

0.875 inches

Center To Center Distance Between Terminals Parallel To Width:

0.625 inches

Nonturn Device Location:

At 3 oclock and at 9 oclock

Nonturn Device Radius:

0.625 inches

0.020 110103

Nonturn Device Length:

0.130 inches

Nonturn Device Diameter:

0.140 inches

Fragility Factor:

Moderately rugged

Mounting Surface To Terminal End Distance:

1.780 inches

Pole Quantity:

2

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

1 threaded bushing w/panel seal

Storage Type:

General purpose warehouse

Special Handling Feature:

Magnetic

Features Provided:

High inrush protection

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

10.0 amperes ac all locations

NSN 5925-01-105-0549

Circuit Breaker - Page 2 of 2



Operating Voltage Type And Rating Per Pole In Vo	lts:
240.0 ac all locations	
Maximum Interrupting Capacity Current Type And	Rating Per Pole In Amps:
1000.0 ac all locations	
Circuit Protection Type:	
Overcurrent all locations	
Trip Release Method:	
Magnetic-hydraulic all locations	
Trip Release Characteristic:	
Time delay all locations	
Ultimate Trip Rating Of Continuous Current Rating	Per Pole In Percent:
115.0 all locations	
Reset Method:	
Manual	
Main Contact Tripping Mechanism Type:	
Trip free	
Manual Actuator Type And Quantity:	
1 toggle	
Actuator Function:	
Trip-reset	
Actuator Position Designation:	
Between pole one and two	
Internal Trip Release Configuration:	
Series trip all locations	
Thread Size:	
0.375 inches	
Trip Delay Time In Seconds Per Rated Continuous	Current:
1.150 at 200 pct all locations and 7.000 at 200 pct all	locations
Inclosure Protection Type For Which Designed:	
Hermetically sealed	
Frequency In Hertz:	
50.0 all locations or 60.0 all locations	
Thread Series Designator:	
Unef	
Terminal Type And Quantity:	
4 wire hook	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	

A030a0