

View Online at <https://aerobasegroup.com/nsn/5925-01-107-8009>

**Body Length:**

2.000 inches

**Body Width:**

0.750 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

1.560 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

1.660 inches

**Mounting Surface To Terminal End Distance:**

1.843 inches

**Pole Quantity:**

1

**Mounting Facility Type And Quantity:**

2 threaded hole

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

25.0 amperes dc single location

**Operating Voltage Type And Rating Per Pole In Volts:**

50.0 dc single location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

2000.0 dc single location

**Circuit Protection Type:**

Overcurrent single location

**Trip Release Method:**

Magnetic-hydraulic single location

**Trip Release Characteristic:**

Time delay single location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 single location

**Ultimate Trip Time Per Pole In Seconds:**

50.000 single location

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole one

**Internal Trip Release Configuration:**

Series trip single location

**Thread Size:**

0.138 inches

**Trip Delay Time In Seconds Per Rated Continuous Current:**

0.650 at 200 pct single location and 8.000 at 200 pct single location and 0.150 at 400 pct single location and 1.500 at 400 pct single location and 0.080 at 500 pct single location and 0.800 at 500 pct single location

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

2 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0