

View Online at <https://aerobasegroup.com/nsn/5925-01-108-3053>

Body Style:

Single pole type

Bushing Length:

0.250 inches

Body Length:

Between 1.796 inches and 1.828 inches

Body Width:

1.000 inches

Center To Center Distance Between Terminals Parallel To Length:

1.437 inches

Mounting Surface To Terminal End Distance:

2.250 inches

Pole Quantity:

1

Maximum Continuous Load Current Rating Per Pole:

150.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

36.0 dc single location

Trip Release Method:

Thermal single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Reset Method:

Manual

Manual Actuator Type And Quantity:

1 push-pull

Trip Delay Time In Seconds Per Rated Continuous Current:

15.000 at 200 pct single location and 70.000 at 200 pct single location and 2.000 at 400 pct single location and 12.000 at 400 pct single location and 1.000 at 600 pct single location and 5.000 at 600 pct single location

Trip Release Ambient Temperature Rating:

-40.0 degrees celsius single location and 71.0 degrees celsius single location

Frequency In Hertz:

60.0 single location

Terminal Type And Quantity:

2 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0