

View Online at <https://aerobasegroup.com/nsn/5925-01-111-6719>

**Body Style:**

Multipole-single actuator type

**Bushing Length:**

0.250 inches

**Body Height:**

1.900 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

0.750 inches

**Pole Quantity:**

3

**Mounting Facility Type And Quantity:**

1 threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

20.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

205.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

1000.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Thermal all locations

**Trip Release Characteristic:**

Instantaneous all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

160.0 all locations

**Ultimate Trip Time Per Pole In Seconds:**

0.350 all locations and 1.400 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 push button

**Actuator Function:**

Reset

**Actuator Position Designation:**

At pole two

**Thread Size:**

0.469 inches

**Inclosure Protection Type For Which Designed:**

Shock resistant and vibrationproof

**Trip Release Ambient Temperature Rating:**

-54.0 degrees celsius all locations and 71.0 degrees celsius all locations

**Thread Tolerance Class:**

2b external

**Special Features:**

Terminals seperated by barriers; amper rating marked on actuator

**Frequency In Hertz:**

400.0 all locations

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

6 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0