

View Online at <https://aerobasegroup.com/nsn/5925-01-112-4403>

Body Style:

Multipole-multiple actuator type

Body Length:

2.490 inches

Body Width:

1.500 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

1.940 inches

Center To Center Distance Between Terminals Parallel To Width:

0.750 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.060 inches

Switch Contact Arrangement:

Single pole, double throw

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.750 inches

Boss Height:

0.150 inches

Mounting Surface To Terminal End Distance:

2.506 inches

Pole Quantity:

2

Mounting Facility Type And Quantity:

4 threaded hole

Features Provided:

Sliding bar interlock

Maximum Continuous Load Current Rating Per Pole:

5.0 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

65.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic-hydraulic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Ultimate Trip Time Per Pole In Seconds:

100.000 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

2 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At each pole

External Actuator Linkage Arrangement:

One and two linked

Auxiliary Switch Function And Quantity:

1 alarm

Internal Trip Release Configuration:

Series trip all locations

Thread Size:

3.0 millimeters

Thread Pitch In Millimeters:

0.50

Switch Location And Position Designation:

External at pole one

Trip Delay Time In Seconds Per Rated Continuous Current:

0.620 at 200 pct all locations and 15.000 at 200 pct all locations and 0.150 at 400 pct all locations and 1.500 at 400 pct all locations and 0.030 at 600 pct all locations and 0.500 at 600 pct all locations

Inclosure Protection Type For Which Designed:

Dustproof and fungus proof and moisture resistant and salt spray proof

Switch Terminal Type:

Tab, solder lug

Switch Current Rating And Type In Amps:

10.0 ac

Switch Voltage Rating And Type In Volts:

250.0 ac

Thread Tolerance Class:

-3 external

Special Features:

Black handle

Thread Series Designator:

Iso m

Terminal Type And Quantity:

4 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0