

View Online at <https://aerobasegroup.com/nsn/5925-01-114-8254>

Body Style:

Single pole type

Body Length:

2.000 inches

Body Width:

0.750 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

1.530 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.666 inches

End Application:

Console distribution panel board onboard 41 ft utb cg vessels

Mounting Surface To Terminal End Distance:

2.390 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

2 threaded hole

Maximum Continuous Load Current Rating Per Pole:

5.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

65.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal-magnetic single location

Trip Release Characteristic:

Instantaneous single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Ultimate Trip Time Per Pole In Seconds:

0.500 single location and 6.500 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Thread Size:

0.137 inches

Inclosure Protection Type For Which Designed:

Vibration resistant and moisture resistant and fungus resistant and corrosion resistant

Trip Release Ambient Temperature Rating:

-40.0 degrees celsius single location and 85.0 degrees celsius single location

Special Features:

Item is equipped with rocker arm type actuator

Thread Series Designator:

Unc

Terminal Type And Quantity:

1 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0