NSN 5925-01-117-8169



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-01-117-8169 **Body Style:** Single pole type **Body Length:** 2.000 inches **Body Width:** 0.625 inches **Body Height:** 1.770 inches **Case Material: Plastic Boss Height:** 0.125 inches **Pole Quantity: Mounting Facility Type And Quantity:** 2 clip Storage Type: General purpose warehouse **Maximum Continuous Load Current Rating Per Pole:** 15.0 amperes ac single location **Operating Voltage Type And Rating Per Pole In Volts:** 250.0 ac single location **Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:** 1000.0 ac single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Magnetic-hydraulic single location **Trip Release Characteristic:** Time delay single location **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 single location **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

NSN 5925-01-117-8169

Circuit Breaker - Page 2 of 2



Internal Trip Release Configuration:

Series trip single location

Trip Delay Time In Seconds Per Rated Continuous Current:

3.000 at 200 pct single location and 30.000 at 200 pct single location

Inclosure Protection Type For Which Designed:

Fungus resistant and moisture resistant

Frequency In Hertz:

50.0 single location or 60.0 single location

Terminal Type And Quantity:

2 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0