NSN 5925-01-118-2484

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-118-2484

| Body Style: |
|--|
| Single pole type |
| Overall Length: |
| 3.764 inches |
| Overall Height: |
| 4.750 inches |
| Overall Width: |
| 1.025 inches |
| Body Length: |
| 4.750 inches |
| Body Width: |
| 1.025 inches |
| Case Material: |
| Plastic |
| Center To Center Distance Between Terminals Parallel To Length: |
| 3.547 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |
| 2.750 inches |
| End Application: |
| Used on ships service switch on baord 140' wtgb c.G. Vessels |
| Boss Height: |
| 0.218 inches |
| Mounting Surface To Terminal End Distance: |
| 3.546 inches |
| Pole Quantity: |
| 1 |
| Mounting Facility Type And Quantity: |
| 2 threaded hole |
| Maximum Continuous Load Current Rating Per Pole: |
| 35.0 milliamperes dc single location |
| Operating Voltage Type And Rating Per Pole In Volts: |
| 35.0 dc single location |
| Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: |
| 35.0 dc single location |
| Circuit Protection Type: |
| Overvoltage single location |
| Trip Release Method: |
| Magnetic single location |
| Trip Release Characteristic: |
| Instantaneous single location |
| Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: |

140.0 all locations

NSN 5925-01-118-2484Circuit Breaker - Page 2 of 2



| Reset Method: |
|---|
| Manual |
| Main Contact Tripping Mechanism Type: |
| Trip free |
| Internal Trip Release Configuration: |
| Relay trip single location |
| Thread Size: |
| 0.190 inches |
| Special Features: |
| Breaker has four terminals in back two for coil, for one line, one for load |
| Thread Series Designator: |
| Unc |
| Terminal Type And Quantity: |
| 4 threaded stud |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| No |
| Fiig: |
| A030a0 |
| |