## NSN 5925-01-118-2484

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-118-2484

| Body Style:  |
|--|
| Single pole type   |
| Overall Length:  |
| 3.764 inches   |
| Overall Height:  |
| 4.750 inches   |
| Overall Width:   |
| 1.025 inches   |
| Body Length:   |
| 4.750 inches   |
| Body Width:  |
| 1.025 inches   |
| Case Material:   |
| Plastic  |
| Center To Center Distance Between Terminals Parallel To Length:              |
| 3.547 inches   |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |
| 2.750 inches   |
| End Application:   |
| Used on ships service switch on baord 140' wtgb c.G. Vessels                 |
| Boss Height:   |
| 0.218 inches   |
| Mounting Surface To Terminal End Distance:                                   |
| 3.546 inches   |
| Pole Quantity:   |
| 1  |
| Mounting Facility Type And Quantity:   |
| 2 threaded hole  |
| Maximum Continuous Load Current Rating Per Pole:                             |
| 35.0 milliamperes dc single location   |
| Operating Voltage Type And Rating Per Pole In Volts:                         |
| 35.0 dc single location  |
| Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:      |
| 35.0 dc single location  |
| Circuit Protection Type:   |
| Overvoltage single location  |
| Trip Release Method:   |
| Magnetic single location   |
| Trip Release Characteristic:   |
| Instantaneous single location  |
| Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:       |

140.0 all locations

## **NSN 5925-01-118-2484**Circuit Breaker - Page 2 of 2



| Reset Method:   |
|---|
| Manual  |
| Main Contact Tripping Mechanism Type:                                       |
| Trip free   |
| Internal Trip Release Configuration:  |
| Relay trip single location  |
| Thread Size:  |
| 0.190 inches  |
| Special Features:   |
| Breaker has four terminals in back two for coil, for one line, one for load |
| Thread Series Designator:   |
| Unc   |
| Terminal Type And Quantity:   |
| 4 threaded stud   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
| <del>-</del>  |
| Demilitarization:   |
| No  |
| Fiig:   |
| A030a0  |
|   |