NSN 5925-01-118-3866

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-118-3866

| Body Style: |
|---|
| Multipole-single actuator type |
| Bushing Length: |
| 0.250 inches |
| Body Length: |
| 2.060 inches |
| Body Width: |
| 1.376 inches |
| Body Height: |
| 1.900 inches |
| Case Material: |
| Plastic |
| Center To Center Distance Between Terminals Parallel To Length: |
| 0.750 inches |
| Center To Center Distance Between Terminals Parallel To Width: |
| 0.688 inches |
| Fragility Factor: |
| Moderately rugged |
| Pole Quantity: |
| 3 |
| Mounting Facility Type And Quantity: |
| 1 threaded bushing |
| Storage Type: |
| General purpose warehouse |
| Thready Qty Per Inch (tpi): |
| 32 |
| Maximum Continuous Load Current Rating Per Pole: |
| 5.0 amperes ac all locations |
| Operating Voltage Type And Rating Per Pole In Volts: |
| 205.0 ac all locations |
| Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: |
| 1000.0 ac all locations |
| Circuit Protection Type: |
| Overcurrent all locations |
| Trip Release Method: |
| Thermal all locations |
| Trip Release Characteristic: |
| Instantaneous all locations |
| Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: |
| 160.0 all locations |

Ultimate Trip Time Per Pole In Seconds:

0.350 all locations and 1.400 all locations

NSN 5925-01-118-3866 Circuit Breaker - Page 2 of 2



| Reset Method: |
|--|
| Manual |
| Main Contact Tripping Mechanism Type: |
| Trip free |
| Manual Actuator Type And Quantity: |
| 1 toggle |
| Actuator Function: |
| Trip-reset |
| Actuator Position Designation: |
| At pole two |
| Internal Trip Release Configuration: |
| Series trip all locations |
| Thread Size: |
| 0.469 inches |
| Inclosure Protection Type For Which Designed: |
| Dustproof and vibrationproof |
| Trip Release Ambient Tempurature Rating: |
| -54.0 degrees celsius all locations and 71.0 degrees celsius all locations |
| Special Features: |
| Terminals seperated by barriers; amper rating marked on actuator |
| Frequency In Hertz: |
| 400.0 all locations |
| Thread Series Designator: |
| Uns |
| Terminal Type And Quantity: |
| 6 threaded stud |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A030a0 |
| |