

View Online at <https://aerobasegroup.com/nsn/5925-01-118-3866>

Body Style:

Multipole-single actuator type

Bushing Length:

0.250 inches

Body Length:

2.060 inches

Body Width:

1.376 inches

Body Height:

1.900 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

0.750 inches

Center To Center Distance Between Terminals Parallel To Width:

0.688 inches

Fragility Factor:

Moderately rugged

Pole Quantity:

3

Mounting Facility Type And Quantity:

1 threaded bushing

Storage Type:

General purpose warehouse

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

5.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

205.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal all locations

Trip Release Characteristic:

Instantaneous all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

160.0 all locations

Ultimate Trip Time Per Pole In Seconds:

0.350 all locations and 1.400 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole two

Internal Trip Release Configuration:

Series trip all locations

Thread Size:

0.469 inches

Inclosure Protection Type For Which Designed:

Dustproof and vibrationproof

Trip Release Ambient Temperature Rating:

-54.0 degrees celsius all locations and 71.0 degrees celsius all locations

Special Features:

Terminals seperated by barriers; amper rating marked on actuator

Frequency In Hertz:

400.0 all locations

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0