NSN 5925-01-119-1103

Circuit Breaker - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5925-01-119-1103

Thread Pitch Diameters:

+0.3503/+0.3537 inches

Body Style:

Multipole-single actuator type

Bushing Length:

0.380 inches

Body Length:

1.562 inches

Body Width:

1.281 inches

Case Material:

Metal

Center To Center Distance Between Terminals Parallel To Length:

Between 0.860 inches and 0.890 inches

Center To Center Distance Between Terminals Parallel To Width:

Between 0.610 inches and 0.640 inches

Nonturn Device Location:

At 3 oclock and at 9 oclock

Nonturn Device Radius:

0.625 inches

Nonturn Device Length:

0.130 inches

Nonturn Device Diameter:

0.140 inches

Fragility Factor:

Moderately rugged

Mounting Surface To Terminal End Distance:

1.780 inches

Pole Quantity:

2

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

1 threaded bushing w/panel seal

Storage Type:

General purpose warehouse

Special Handling Feature:

Magnetic

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

2.5 amperes ac all locations

NSN 5925-01-119-1103

Circuit Breaker - Page 2 of 3



_	
	Operating Voltage Type And Rating Per Pole In Volts:
	240.0 ac all locations
	Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
	1000.0 ac all locations
	Circuit Protection Type:
	Overcurrent all locations
	Trip Release Method:
	Magnetic all locations
	Trip Release Characteristic:
	Time delay all locations
	Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
	115.0 all locations
	Reset Method:
	Manual
	Main Contact Tripping Mechanism Type:
	Trip free
	Manual Actuator Type And Quantity:
	1 toggle
	Actuator Function:
	Trip-reset
	Actuator Position Designation:
	Between pole one and two
	Internal Trip Release Configuration:
	Series trip all locations
	Thread Size:
	0.375 inches
	Trip Delay Time In Seconds Per Rated Continuous Current:
	0.800 at 200 pct all locations and 8.000 at 200 pct all locations
	Inclosure Protection Type For Which Designed:
	Hermetically sealed
	Frequency In Hertz:
	50.0 all locations or 60.0 all locations
	Unpackaged Unit Weight:
	3.600 ounces
	Thread Series Designator:
	Unef
	Terminal Type And Quantity:
	4 wire hook
	Shelf Life:
	N/a
	Unit Of Measure:
	Demilitarization:

No

NSN 5925-01-119-1103

Circuit Breaker - Page 3 of 3

Fiig: A030a0

