NSN 5925-01-119-4393



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-01-119-4393 **Body Style:** Rectangular dimensional envelope **Overall Length:** 13.000 inches **Overall Height:** 6.620 inches **Overall Width:** 8.250 inches **Case Material: Plastic Unthreaded Mounting Hole Diameter:** 0.164 inches **Pole Quantity: Mounting Facility Type And Quantity:** 4 unthreaded hole Storage Type: General purpose warehouse **Maximum Continuous Load Current Rating Per Pole:** 20.0 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:** 208.0 ac all locations **Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:** 10000.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Thermal-magnetic all locations **Trip Release Characteristic:** Time delay all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 150.0 all locations **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free **Manual Actuator Type And Quantity:** 1 toggle **Actuator Function:**

Actuator Position Designation: At pole two

Trip-reset

NSN 5925-01-119-4393

Circuit Breaker - Page 2 of 2



Trip Delay Time In Seconds Per Rated Continuous Current:

30.000 at 200 pct all locations and 100.000 at 200 pct all locations

Trip Release Ambient Tempurature Rating:

40.0 degrees celsius all locations

Frequency In Hertz:

60.0 all locations

Terminal Type And Quantity:

6 compression

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0