

View Online at <https://aerobasegroup.com/nsn/5925-01-120-0886>

Body Style:

Rectangular dimensional envelope

Overall Length:

27.000 inches

Overall Height:

22.250 inches

Overall Width:

20.380 inches

Case Material:

Metal

Unthreaded Mounting Hole Diameter:

0.690 inches

End Application:

S/s switchboard aboard 140 ft wtgb class coast guard vessels

Pole Quantity:

3

Mounting Facility Type And Quantity:

4 unthreaded hole

Maximum Continuous Load Current Rating Per Pole:

400.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

440.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

42000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Solid state all locations

Trip Release Characteristic:

Instantaneous all locations and time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Electric

Main Contact Tripping Mechanism Type:

Trip free

Reset Actuator Voltage Rating And Type In Volts:

120.0 ac

Trip Delay Time In Seconds Per Rated Continuous Current:

22.000 at 125 pct all locations

Special Features:

Circuit breaker is a drawout type equipped with long and short time instantaneous trip; 120vac shunt trip w/remote release; 6 stage aux switches w/6no-6nc contacts

Frequency In Hertz:

60.0 all locations

Terminal Type And Quantity:

6 bus bar

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0