

View Online at <https://aerobasegroup.com/nsn/5925-01-120-0886>

**Body Style:**

Rectangular dimensional envelope

**Overall Length:**

27.000 inches

**Overall Height:**

22.250 inches

**Overall Width:**

20.380 inches

**Case Material:**

Metal

**Unthreaded Mounting Hole Diameter:**

0.690 inches

**End Application:**

S/s switchboard aboard 140 ft wtgb class coast guard vessels

**Pole Quantity:**

3

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Maximum Continuous Load Current Rating Per Pole:**

400.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

440.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

42000.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Solid state all locations

**Trip Release Characteristic:**

Instantaneous all locations and time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Reset Method:**

Electric

**Main Contact Tripping Mechanism Type:**

Trip free

**Reset Actuator Voltage Rating And Type In Volts:**

120.0 ac

**Trip Delay Time In Seconds Per Rated Continuous Current:**

22.000 at 125 pct all locations

**Special Features:**

Circuit breaker is a drawout type equipped with long and short time instantaneous trip; 120vac shunt trip w/remote release; 6 stage aux switches w/6no-6nc contacts

**Frequency In Hertz:**

60.0 all locations

**Terminal Type And Quantity:**

6 bus bar

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0