

View Online at <https://aerobasegroup.com/nsn/5925-01-120-0888>

Body Style:

Single pole type

Bushing Length:

0.250 inches

Body Length:

1.260 inches

Body Width:

0.730 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

0.900 inches

Nonturn Device Location:

At 12 oclock

Nonturn Device Radius:

0.370 inches

Nonturn Device Length:

0.060 inches

Nonturn Device Width:

0.110 inches

Fragility Factor:

Moderately rugged

Mounting Surface To Terminal End Distance:

2.520 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

1 threaded bushing w/panel seal

Storage Type:

General purpose warehouse

Maximum Continuous Load Current Rating Per Pole:

35.0 amperes ac single location and 35.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

115.0 ac single location and 28.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

2000.0 ac single location and 2000.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

140.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 push-pull

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Internal Trip Release Configuration:

Series trip single location

Thread Size:

12.0 millimeters

Thread Pitch In Millimeters:

1.75

Trip Delay Time In Seconds Per Rated Continuous Current:

12.000 at 200 pct single location and 80.000 at 200 pct single location

Inclosure Protection Type For Which Designed:

Fungus resistant and moisture resistant

Trip Release Ambient Temperature Rating:

70.0 degrees fahrenheit single location

Frequency In Hertz:

400.0 single location

Unpackaged Unit Weight:

2.300 ounces

Thread Series Designator:

Iso m

Terminal Type And Quantity:

2 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0