## NSN 5925-01-120-0888

Circuit Breaker - Page 1 of 2

**Body Style:** 



View Online at https://aerobasegroup.com/nsn/5925-01-120-0888

Single pole type
Bushing Length:
0.250 inches
Body Length:
1.260 inches
Body Width:
0.730 inches
Case Material:
Plastic
Center To Center Distance Between Terminals Parallel To Length:
0.900 inches
Nonturn Device Location:
At 12 oclock
Nonturn Device Radius:
0.370 inches
Nonturn Device Length:
0.060 inches
Nonturn Device Width:
0.110 inches
Fragility Factor:
Moderately rugged
Mounting Surface To Terminal End Distance:
2.520 inches
Pole Quantity:
1
Mounting Facility Type And Quantity:
1 threaded bushing w/panel seal
Storage Type:
General purpose warehouse
Maximum Continuous Load Current Rating Per Pole:
35.0 amperes ac single location and 35.0 amperes dc single location
Operating Voltage Type And Rating Per Pole In Volts:
115.0 ac single location and 28.0 dc single location
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
2000.0 ac single location and 2000.0 dc single location
Circuit Protection Type:
Overcurrent single location
Trip Release Method:
Thermal single location
Trip Release Characteristic:
Time delay single location

## **NSN 5925-01-120-0888** Circuit Breaker - Page 2 of 2



Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
140.0 single location
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 push-pull
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole one
Internal Trip Release Configuration:
Series trip single location
Thread Size:
12.0 millimeters
Thread Pitch In Millimeters:
1.75
Trip Delay Time In Seconds Per Rated Continuous Current:
12.000 at 200 pct single location and 80.000 at 200 pct single location
Inclosure Protection Type For Which Designed:
Fungus resistant and moisture resistant
Trip Release Ambient Tempurature Rating:
70.0 degrees fahrenheit single location
Frequency In Hertz:
400.0 single location
Unpackaged Unit Weight:
2.300 ounces
Thread Series Designator:
Iso m
Terminal Type And Quantity:
2 tab w/screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0