NSN 5925-01-121-8074

Circuit Breaker Tripper - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5925-01-121-8074

Body Style:

Cylindrical dimensional envelope

Overall Length:

3.500 inches

Overall Diameter:

0.312 inches

End Application:

5925-00-975-3924, circuit breaker used on ships service switchboard onboard 270 ft wmec coast guard vessels

Pole Quantity:

```
1
```

Mounting Facility Type And Quantity:

1 unthreaded hole

Maximum Continuous Load Current Rating Per Pole:

18.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

125.0 dc single location

Circuit Protection Type:

Undervoltage single location

Trip Release Method:

Magnetic single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Internal Trip Release Configuration:

Relay trip single location

Special Features:

Time delay 0.1 to 0.5 seconds; trips breaker at 30 to 60% rated voltage; unef thread on mounting

Terminal Type And Quantity:

2 wire lead

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A030a0