

View Online at <https://aerobasegroup.com/nsn/5925-01-121-9398>

Body Style:

Rectangular dimensional envelope

Overall Length:

3.625 inches

Overall Height:

1.625 inches

Overall Width:

2.578 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.203 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

2 unthreaded hole

Maximum Continuous Load Current Rating Per Pole:

25.0 amperes ac single location and 25.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

120.0 ac single location and 28.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

4000.0 ac single location and 4000.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

138.0 single location

Reset Method:

Automatic

Internal Trip Release Configuration:

Series trip single location

Trip Delay Time In Seconds Per Rated Continuous Current:

10.000 at 200 pct single location and 70.000 at 200 pct single location

Inclosure Protection Type For Which Designed:

Vibration resistant and shock resistant and explosion proof and sand resistant and corrosion resistant

Trip Release Ambient Temperature Rating:

77.0 degrees fahrenheit single location

Frequency In Hertz:

60.0 single location or 1000.0 single location

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0