

View Online at <https://aerobasegroup.com/nsn/5925-01-122-1524>

Body Style:

Multipole-single actuator type

Bushing Length:

Between 0.332 inches and 0.375 inches

Body Length:

1.500 inches

Body Width:

1.875 inches

Case Material:

Metal

Center To Center Distance Between Terminals Parallel To Length:

Between 0.844 inches and 0.906 inches

Center To Center Distance Between Terminals Parallel To Width:

Between 0.595 inches and 0.656 inches

Nonturn Device Location:

At 3 oclock and at 9 oclock

Nonturn Device Diameter:

0.250 inches

Switch Contact Arrangement:

Single pole, double throw

Mounting Surface To Terminal End Distance:

1.780 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

1 threaded bushing w/panel seal

Storage Type:

General purpose warehouse

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

20.0 amperes ac third location

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac third location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

300.0 ac second location

Circuit Protection Type:

Overvoltage first location

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Time delay third location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

115.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole two

Auxiliary Switch Function And Quantity:

1 alarm

Internal Trip Release Configuration:

Series trip third location

Thread Size:

0.375 inches

Switch Location And Position Designation:

Internal at pole three

Trip Delay Time In Seconds Per Rated Continuous Current:

0.500 at 200 pct third location and 9.000 at 200 pct third location

Inclosure Protection Type For Which Designed:

Hermetically sealed and moisture resistant and salt spray proof and shockproof and vibrationproof

Switch Terminal Type:

Quick disconnect, male

Switch Current Rating And Type In Amps:

0.5 ac

Switch Voltage Rating And Type In Volts:

125.0 ac

Special Features:

No current on pole one

Frequency In Hertz:

60.0 all locations

Thread Series Designator:

Unef

Terminal Type And Quantity:

6 wire hook and 2 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0