

View Online at <https://aerobasegroup.com/nsn/5925-01-122-5268>

Body Style:

Multipole-multiple actuator type

Body Length:

3.281 inches

Body Width:

2.000 inches

Body Height:

2.359 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Width:

1.000 inches

End Application:

Panel board 54313 onboard 270 ft wmec coast guard vessels

Boss Height:

0.140 inches

Pole Quantity:

2

Mounting Facility Type And Quantity:

4 terminal

Maximum Continuous Load Current Rating Per Pole:

70.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

10000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

135.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

2 toggle

Actuator Function:

Trip-reset

Trip Delay Time In Seconds Per Rated Continuous Current:

18.000 at 200 pct all locations and 125.000 at 200 pct all locations

Trip Release Ambient Temperature Rating:

50.0 degrees celsius all locations

Frequency In Hertz:

60.0 all locations

Terminal Type And Quantity:

4 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0