NSN 5925-01-122-6602

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-122-6602

## **Body Style:**

Multipole-single actuator type

#### **Body Length:**

6.000 inches

## Body Width:

4.469 inches

## **Body Height:**

3.156 inches

#### **Case Material:**

Plastic

## Center To Center Distance Between Terminals Parallel To Length:

#### 5.125 inches

Center To Center Distance Between Terminals Parallel To Width:

#### 1.500 inches

**Unthreaded Mounting Hole Diameter:** 

#### 0.172 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

5.125 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.500 inches

## Boss Height:

0.125 inches

#### Pole Quantity:

3

# Mounting Facility Type And Quantity:

4 unthreaded hole

## Storage Type:

General purpose warehouse

# Maximum Continuous Load Current Rating Per Pole:

30.0 amperes ac all locations and 30.0 amperes dc all locations

# Operating Voltage Type And Rating Per Pole In Volts:

600.0 ac all locations and 250.0 dc all locations

# Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

15000.0 ac all locations and 10000.0 dc all locations

## Circuit Protection Type:

Overcurrent all locations

# Trip Release Method:

Thermal-magnetic all locations

# Trip Release Characteristic:

Time delay all locations

## Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

# NSN 5925-01-122-6602

Circuit Breaker - Page 2 of 2



lanual	
lain Contact Tripping Mechanism Type:	
rip free	
lanual Actuator Type And Quantity:	
toggle	
ctuator Function:	
rip-reset	
ctuator Position Designation:	
t pole two	
rip Delay Time In Seconds Per Rated Continuous Current	t:
0.000 at 200 pct all locations and 100.000 at 200 pct all loca	ations
closure Protection Type For Which Designed:	
ustproof	
rip Release Ambient Tempurature Rating:	
0.0 degrees celsius all locations	
requency In Hertz:	
0.0 all locations	
erminal Type And Quantity:	
compression	
helf Life:	
/a	
nit Of Measure:	
emilitarization:	
0	
iig:	
030a0	