

View Online at <https://aerobasegroup.com/nsn/5925-01-122-7569>

Body Style:

Multipole-single actuator type

Body Length:

2.000 inches

Body Width:

1.540 inches

Body Height:

1.770 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Width:

0.625 inches

End Application:

Missile, minuteman Igm-30; mx peacekeeper

Boss Height:

0.250 inches

Pole Quantity:

2

Mounting Facility Type And Quantity:

4 clip

Storage Type:

General purpose warehouse

Special Handling Feature:

Magnetic

Maximum Continuous Load Current Rating Per Pole:

8.0 amperes ac second location

Operating Voltage Type And Rating Per Pole In Volts:

277.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic-hydraulic first location

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

Between pole one and two

Internal Trip Release Configuration:

Shunt trip second location

Trip Delay Time In Seconds Per Rated Continuous Current:

0.500 at 200 pct all locations and 8.000 at 200 pct all locations

Criticality Code Justification:

Feat

Special Features:

Weapon system essential

Frequency In Hertz:

60.0 all locations

Terminal Type And Quantity:

5 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0