## NSN 5925-01-123-0756

Circuit Breaker - Page 1 of 2

**Body Length:** 



View Online at https://aerobasegroup.com/nsn/5925-01-123-0756

10.125 inches
Body Width:
4.000 inches
Body Height:
3.380 inches
Case Material:
Plastic
Center To Center Distance Between Terminals Parallel To Length:
8.375 inches
Center To Center Distance Between Terminals Parallel To Width:
2.750 inches
Unthreaded Mounting Hole Diameter:
0.312 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
7.750 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.375 inches
Boss Height:
0.240 inches
Pole Quantity:
2
Mounting Facility Type And Quantity:
4 unthreaded hole
Storage Type:
General purpose warehouse
Features Provided:
Adjustable trip release
Maximum Continuous Load Current Rating Per Pole:
110.0 amperes ac all locations and 110.0 amperes dc all locations
Operating Voltage Type And Rating Per Pole In Volts:
600.0 ac all locations and 250.0 dc all locations
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
22000.0 ac all locations and 20000.0 dc all locations
Circuit Protection Type:
Overcurrent all locations
Trip Release Method:
Thermal-magnetic all locations

125.0 all locations

**Trip Release Characteristic:** 

Instantaneous all locations and time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 

## NSN 5925-01-123-0756

Circuit Breaker - Page 2 of 2



Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
Between pole one and two
Adjustable Trip Setting Current Range Per Pole In Amps:
+600.0/+1250.0 ac all locations and +600.0/+1250.0 dc all locations
Trip Delay Time In Seconds Per Rated Continuous Current:
0.024 at 200 pct all locations and 9.000 at 200 pct all locations
nclosure Protection Type For Which Designed:
Fungus resistant
Trip Release Ambient Tempurature Rating:
40.0 degrees celsius all locations
Frequency In Hertz:
60.0 all locations
Terminal Type And Quantity:
4 compression
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
4030a0