NSN 5925-01-124-8485



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-01-124-8485 **Body Style:** Multipole-single actuator type **Bushing Length:** 0.380 inches **Body Length:** 1.500 inches **Body Width:** 1.250 inches **Case Material:** Metal **Center To Center Distance Between Terminals Parallel To Length:** 0.875 inches **Center To Center Distance Between Terminals Parallel To Width:** 0.625 inches **Nonturn Device Location:** At 3 oclock and at 9 oclock **Nonturn Device Radius:** Between 0.594 inches and 0.656 inches **Nonturn Device Diameter:** Between 0.157 inches and 0.219 inches **Fragility Factor:** Moderately rugged **Mounting Surface To Terminal End Distance:** 1.780 inches **Pole Quantity:** 2 **Arc Quenching Method:** Magnetic blowout **Mounting Facility Type And Quantity:** 1 threaded bushing w/panel seal Storage Type: General purpose warehouse **Special Handling Feature:**

Magnetic

Features Provided:

High inrush protection

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

50.0 milliamperes ac second location

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac all locations

NSN 5925-01-124-8485

Circuit Breaker - Page 2 of 2



Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
1000.0 ac all locations
Circuit Protection Type:
Overcurrent all locations
Trip Release Method:
Magnetic all locations
Trip Release Characteristic:
Time delay all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
125.0 all locations
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
Between pole one and two
Internal Trip Release Configuration:
Series trip all locations
Thread Size:
0.375 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
10.500 at 200 pct second location and 60.000 at 200 pct second location
Inclosure Protection Type For Which Designed:
Hermetically sealed and vibration resistant and shock resistant
Frequency In Hertz:
60.0 all locations
Unpackaged Unit Weight:
3.600 ounces
Thread Series Designator:
Unef
Terminal Type And Quantity:
4 wire hook
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A030a0