

View Online at <https://aerobasegroup.com/nsn/5925-01-124-9624>

**Body Style:**

Multipole-single actuator type

**Body Length:**

22.000 inches

**Body Width:**

12.000 inches

**Body Height:**

12.243 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

14.375 inches

**Center To Center Distance Between Terminals Parallel To Width:**

4.000 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

13.625 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

4.000 inches

**Boss Height:**

0.813 inches

**Pole Quantity:**

3

**Mounting Facility Type And Quantity:**

4 threaded stud

**Storage Type:**

General purpose warehouse

**Features Provided:**

Adjustable trip release

**Thready Qty Per Inch (tpi):**

16

**Maximum Continuous Load Current Rating Per Pole:**

1200.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

500.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

50000.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Thermal-magnetic all locations

**Trip Release Characteristic:**

Instantaneous all locations and time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

140.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole two

**Adjustable Trip Setting Current Range Per Pole In Amps:**

+2000.0/+6000.0 ac all locations

**Thread Size:**

0.375 inches

**Trip Delay Time In Seconds Per Rated Continuous Current:**

0.041 at 200 pct all locations and 0.045 at 200 pct all locations

**Inclosure Protection Type For Which Designed:**

Fungus resistant

**Trip Release Ambient Temperature Rating:**

40.0 degrees celsius all locations

**Frequency In Hertz:**

60.0 all locations

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

6 quick disconnect, male

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0