NSN 5925-01-124-9624

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-124-9624

## **Body Style:**

Multipole-single actuator type

## **Body Length:**

22.000 inches

# Body Width:

12.000 inches

## **Body Height:**

12.243 inches

#### **Case Material:**

Plastic

#### Center To Center Distance Between Terminals Parallel To Length:

#### 14.375 inches

Center To Center Distance Between Terminals Parallel To Width:

#### 4.000 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

#### 13.625 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

## 4.000 inches

**Boss Height:** 

0.813 inches

## **Pole Quantity:**

3

## Mounting Facility Type And Quantity:

4 threaded stud

#### Storage Type:

General purpose warehouse

#### **Features Provided:**

Adjustable trip release

#### Thready Qty Per Inch (tpi):

16

#### Maximum Continuous Load Current Rating Per Pole:

1200.0 amperes ac all locations

## **Operating Voltage Type And Rating Per Pole In Volts:**

500.0 ac all locations

#### Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

50000.0 ac all locations

## **Circuit Protection Type:**

Overcurrent all locations

#### **Trip Release Method:**

Thermal-magnetic all locations

#### **Trip Release Characteristic:**

Instantaneous all locations and time delay all locations

# NSN 5925-01-124-9624

Circuit Breaker - Page 2 of 2



## Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

140.0 all locations

## **Reset Method:**

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

**Actuator Function:** 

Trip-reset

**Actuator Position Designation:** 

At pole two

## Adjustable Trip Setting Current Range Per Pole In Amps:

+2000.0/+6000.0 ac all locations

## Thread Size:

0.375 inches

## Trip Delay Time In Seconds Per Rated Continuous Current:

0.041 at 200 pct all locations and 0.045 at 200 pct all locations

# Inclosure Protection Type For Which Designed:

Fungus resistant

Trip Release Ambient Tempurature Rating:

40.0 degrees celsius all locations

Frequency In Hertz:

60.0 all locations

# **Thread Series Designator:**

Unc

## **Terminal Type And Quantity:**

6 quick disconnect, male

Shelf Life:

N/a

## Unit Of Measure:

---

#### **Demilitarization:**

No

# Fiig:

A030a0