

View Online at <https://aerobasegroup.com/nsn/5925-01-125-4368>

Thread Pitch Diameters:

+0.1177/+0.1214 inches

Body Style:

Multipole-multiple actuator type

Body Length:

2.000 inches

Body Width:

1.515 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

1.530 inches

Center To Center Distance Between Terminals Parallel To Width:

0.750 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.660 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.750 inches

Fragility Factor:

Moderately rugged

Boss Height:

0.130 inches

Mounting Surface To Terminal End Distance:

2.000 inches

Pole Quantity:

2

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

4 threaded hole

Storage Type:

General purpose warehouse

Special Handling Feature:

Magnetic

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

5.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic-hydraulic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

115.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

2 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At each pole

External Actuator Linkage Arrangement:

One and two linked

Internal Trip Release Configuration:

Series trip all locations

Thread Size:

0.138 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

2.000 at 200 pct all locations and 20.000 at 200 pct all locations

Inclosure Protection Type For Which Designed:

Hermetically sealed and shock resistant and vibration resistant

Frequency In Hertz:

60.0 all locations

Unpackaged Unit Weight:

4.400 ounces

Thread Series Designator:

Unc

Terminal Type And Quantity:

4 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0