Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-125-5719

| Bushing | Length: |
|---------|---------|
|         |         |

0.250 inches

Body Length: 0.750 inches

Body Width:

0.562 inches

**Case Material:** 

Plastic

Center To Center Distance Between Terminals Parallel To Length:

0.703 inches

Fragility Factor:

Moderately rugged

Mounting Surface To Terminal End Distance:

1.707 inches

**Pole Quantity:** 

1 **∆r** 

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

1 threaded bushing

Storage Type:

General purpose warehouse

Thready Qty Per Inch (tpi):

32

# Maximum Continuous Load Current Rating Per Pole:

10.0 amperes ac single location and 10.0 amperes dc single location

# **Operating Voltage Type And Rating Per Pole In Volts:**

120.0 ac single location and 28.0 dc single location

# Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

800.0 ac single location and 2000.0 dc single location

### **Circuit Protection Type:**

Overcurrent single location

### **Trip Release Method:**

Thermal single location

### **Trip Release Characteristic:**

Time delay single location

# Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

145.0 single location

**Reset Method:** 

Manual

Main Contact Tripping Mechanism Type:

Trip free

# NSN 5925-01-125-5719

Circuit Breaker - Page 2 of 2



Manual Actuator Type And Quantity: 1 push-pull **Actuator Function:** Trip-reset **Actuator Position Designation:** At pole one Internal Trip Release Configuration: Series trip single location Thread Size: 0.469 inches Trip Delay Time In Seconds Per Rated Continuous Current: 2.000 at 200 pct single location and 20.000 at 200 pct single location **Inclosure Protection Type For Which Designed:** Corrosion resistant and sand resistant **Trip Release Ambient Tempurature Rating:** 25.0 degrees celsius single location **Special Features:** Ampere marked on actuator Frequency In Hertz: 400.0 single location **Unpackaged Unit Weight:** 1.500 ounces **Thread Series Designator:** Uns **Terminal Type And Quantity:** 2 tab w/screw Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig: A030a0