## NSN 5925-01-127-5835



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-01-127-5835 **Body Style:** Single pole type **Body Length:** 2.150 inches **Overall Diameter:** 0.750 inches **Case Material: Plastic Pole Quantity: Mounting Facility Type And Quantity:** 1 clip Storage Type: General purpose warehouse **Maximum Continuous Load Current Rating Per Pole:** 500.0 milliamperes ac single location and 500.0 milliamperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 240.0 ac single location and 32.0 dc single location **Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:** 1000.0 ac single location and 200.0 dc single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Thermal single location **Trip Release Characteristic:** Time delay all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 135.0 single location **Reset Method:** Manual **Main Contact Tripping Mechanism Type: Manual Actuator Type And Quantity:** 1 push button **Actuator Function:** Reset **Actuator Position Designation:** 

At pole one

**Internal Trip Release Configuration:** 

Series trip single location

**Trip Delay Time In Seconds Per Rated Continuous Current:** 

2.500 at 200 pct single location and 10.000 at 200 pct single location

## NSN 5925-01-127-5835

Circuit Breaker - Page 2 of 2



Inclosure	<b>Protection</b>	Type F	or Which	Designed:
ii iciosui e	FIOLECTION	IVDEI	OI WILLIGH	Desidiled.

Fungus resistant

**Trip Release Ambient Tempurature Rating:** 

25.0 degrees celsius single location

Frequency In Hertz:

50.0 single location or 60.0 single location

**Terminal Type And Quantity:** 

2 quick disconnect, male

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A030a0