# NSN 5925-01-128-1072

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-128-1072

### **Body Style:** Single pole type **Body Length:** Between 2.490 inches and 2.510 inches **Body Width:** Between 0.740 inches and 0.760 inches Case Material: Plastic Center To Center Distance Between Terminals Parallel To Length: Between 1.928 inches and 1.948 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: Between 2.052 inches and 2.072 inches **Fragility Factor:** Moderately rugged **Boss Height:** Between 0.740 inches and 0.760 inches Mounting Surface To Terminal End Distance: 2.611 inches **Pole Quantity:** 1 Arc Quenching Method: Magnetic blowout Mounting Facility Type And Quantity: 2 threaded hole Storage Type: General purpose warehouse **Special Handling Feature:** Magnetic **Features Provided:** High inrush protection Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole: 3.0 amperes ac single location **Operating Voltage Type And Rating Per Pole In Volts:** 250.0 ac single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 1000.0 ac single location **Circuit Protection Type:** Overcurrent single location

### **Trip Release Method:**

Magnetic-hydraulic single location

# NSN 5925-01-128-1072

Circuit Breaker - Page 2 of 2



**Trip Release Characteristic:** 

Time delay single location

#### Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

**Reset Method:** 

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

**Actuator Position Designation:** 

At pole one

Internal Trip Release Configuration:

Series trip single location

Thread Size:

0.138 inches

#### Trip Delay Time In Seconds Per Rated Continuous Current:

2.000 at 200 pct single location and 20.000 at 200 pct single location

Inclosure Protection Type For Which Designed:

Fungus resistant

Frequency In Hertz:

60.0 single location

Unpackaged Unit Weight:

4.250 ounces

Thread Series Designator:

Unc

**Terminal Type And Quantity:** 

2 threaded stud

Shelf Life:

N/a

Unit Of Measure:

---

**Demilitarization:** 

No

Fiig:

A030a0