

View Online at <https://aerobasegroup.com/nsn/5925-01-128-2135>

Body Style:

Multipole-multiple actuator type

Body Length:

Between 1.985 inches and 2.015 inches

Body Width:

Between 2.245 inches and 2.255 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

Between 1.555 inches and 1.565 inches

Center To Center Distance Between Terminals Parallel To Width:

Between 0.745 inches and 0.755 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 1.655 inches and 1.665 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.745 inches and 0.755 inches

Fragility Factor:

Moderately rugged

Boss Height:

Between 0.125 inches and 0.135 inches

Mounting Surface To Terminal End Distance:

Between 1.835 inches and 1.845 inches

Pole Quantity:

3

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

3 threaded hole

Storage Type:

General purpose warehouse

Thready Qty Per Inch (tpi):

32

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic-hydraulic all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

3 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At each pole

External Actuator Linkage Arrangement:

One, two, and three linked

Thread Size:

0.138 inches

Inclosure Protection Type For Which Designed:

Dustproof

Thread Series Designator:

Unc

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A030a0