

View Online at <https://aerobasegroup.com/nsn/5925-01-129-3384>

Body Style:

Rectangular dimensional envelope

Overall Length:

2.000 inches

Overall Height:

1.410 inches

Overall Width:

1.563 inches

Case Material:

Plastic and metal

Unthreaded Mounting Hole Diameter:

Between 0.190 inches and 0.225 inches

Fragility Factor:

Moderately rugged

Pole Quantity:

1

Mounting Facility Type And Quantity:

2 unthreaded hole

Storage Type:

General purpose warehouse

Maximum Continuous Load Current Rating Per Pole:

40.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

12.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

200.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Reset Method:

Automatic

Internal Trip Release Configuration:

Series trip single location

Trip Delay Time In Seconds Per Rated Continuous Current:

4.000 at 200 pct single location and 5.000 at 200 pct single location

Inclosure Protection Type For Which Designed:

General purpose

Trip Release Ambient Temperature Rating:

40.0 degrees celsius single location

Special Features:

With 90 degree mounting bracket included

Terminal Type And Quantity:

2 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0