# NSN 5925-01-131-6786

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-131-6786

#### **Body Style:**

Multipole-multiple actuator type

## **Body Length:**

2.490 inches

# Body Width:

1.500 inches

## Case Material:

Plastic

#### Center To Center Distance Between Terminals Parallel To Length:

1.940 inches

#### Center To Center Distance Between Terminals Parallel To Width:

#### 0.750 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

#### 2.060 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

# 0.750 inches

Boss Height:

0.150 inches

# Mounting Surface To Terminal End Distance:

2.625 inches

## **Pole Quantity:**

2

#### Arc Quenching Method:

Magnetic blowout

## Mounting Facility Type And Quantity:

4 threaded hole

#### Storage Type:

General purpose warehouse

#### Thready Qty Per Inch (tpi):

32

#### Maximum Continuous Load Current Rating Per Pole:

6.5 amperes ac all locations

#### **Operating Voltage Type And Rating Per Pole In Volts:**

277.0 ac all locations

#### Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

5000.0 ac all locations

#### **Circuit Protection Type:**

Overcurrent all locations

#### **Trip Release Method:**

Magnetic all locations

#### **Trip Release Characteristic:**

Time delay all locations

Circuit Breaker - Page 2 of 2



## Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

#### **Reset Method:**

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

2 toggle

**Actuator Function:** 

Trip-reset

**Actuator Position Designation:** 

At each pole

External Actuator Linkage Arrangement:

One and two linked

Internal Trip Release Configuration:

Series trip all locations

Thread Size:

0.138 inches

#### Trip Delay Time In Seconds Per Rated Continuous Current:

7.000 at 100 pct all locations

Inclosure Protection Type For Which Designed:

General purpose

**Frequency In Hertz:** 

50.0 all locations or 60.0 all locations

## **Thread Series Designator:**

Unc

#### **Terminal Type And Quantity:**

4 threaded stud

Shelf Life:

N/a

#### Unit Of Measure:

---

#### **Demilitarization:**

No

### Fiig:

A030a0