## NSN 5925-01-131-6787



Circuit Breaker - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5925-01-131-6787

Body Style:
Multipole-multiple actuator type
Body Length:
2.490 inches
Body Width:
1.500 inches
Case Material:
Plastic
Center To Center Distance Between Terminals Parallel To Length:
1.940 inches
Center To Center Distance Between Terminals Parallel To Width:
0.750 inches

0.7 30 11101163

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.060 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.750 inches

**Boss Height:** 

0.150 inches

**Mounting Surface To Terminal End Distance:** 

2.625 inches

**Pole Quantity:** 

2

**Arc Quenching Method:** 

Magnetic blowout

**Mounting Facility Type And Quantity:** 

4 threaded hole

Storage Type:

General purpose warehouse

Thready Qty Per Inch (tpi):

32

**Maximum Continuous Load Current Rating Per Pole:** 

0.75 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

277.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

5000.0 ac all locations

**Circuit Protection Type:** 

Overcurrent all locations

**Trip Release Method:** 

Magnetic all locations

**Trip Release Characteristic:** 

Time delay all locations

## **NSN 5925-01-131-6787** Circuit Breaker - Page 2 of 2



Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
125.0 all locations
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
2 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At each pole
External Actuator Linkage Arrangement:
One and two linked
Internal Trip Release Configuration:
Series trip all locations
Thread Size:
0.138 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
7.000 at 100 pct all locations
Inclosure Protection Type For Which Designed:
General purpose
Frequency In Hertz:
50.0 all locations or 60.0 all locations
Thread Series Designator:
Unc
Terminal Type And Quantity:
4 threaded stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0