NSN 5925-01-131-6791



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-01-131-6791 **Body Style:** Multipole-multiple actuator type **Body Length:** 2.490 inches **Body Width:** 5.250 inches **Case Material:** Plastic **Center To Center Distance Between Terminals Parallel To Length:** 1.940 inches **Center To Center Distance Between Terminals Parallel To Width:** 0.750 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 2.060 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.750 inches **Boss Height:** 0.150 inches **Mounting Surface To Terminal End Distance:** 2.625 inches **Pole Quantity: Mounting Facility Type And Quantity:** 14 threaded hole Thready Qty Per Inch (tpi): 32 **Maximum Continuous Load Current Rating Per Pole:** 5.0 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:** 120.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Magnetic all locations **Trip Release Characteristic:** Time delay all locations **Reset Method:** Manual **Manual Actuator Type And Quantity:** 7 toggle

Actuator Function:

Trip-reset

NSN 5925-01-131-6791 Circuit Breaker - Page 2 of 2



| Internal Trip Release Configuration: |
|--|
| Series trip all locations |
| Thread Size: |
| 0.138 inches |
| Trip Delay Time In Seconds Per Rated Continuous Current: |
| 6.000 at 100 pct all locations |
| Frequency In Hertz: |
| 400.0 all locations |
| Thread Series Designator: |
| Unc |
| Terminal Type And Quantity: |
| 14 threaded stud |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A030a0 |
| |