

View Online at <https://aerobasegroup.com/nsn/5925-01-131-7161>

**Body Style:**

Single pole type

**Body Length:**

2.150 inches

**Overall Diameter:**

0.635 inches

**Case Material:**

Plastic

**Fragility Factor:**

Moderately rugged

**Pole Quantity:**

1

**Arc Quenching Method:**

Air

**Mounting Facility Type And Quantity:**

1 clip

**Storage Type:**

General purpose warehouse

**Maximum Continuous Load Current Rating Per Pole:**

5.0 amperes ac single location and 5.0 amperes dc single location

**Operating Voltage Type And Rating Per Pole In Volts:**

250.0 ac single location and 32.0 dc single location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

1000.0 ac single location and 200.0 dc single location

**Circuit Protection Type:**

Overcurrent single location

**Trip Release Method:**

Thermal single location

**Trip Release Characteristic:**

Time delay single location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

135.0 single location

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 push button

**Actuator Function:**

Reset

**Actuator Position Designation:**

At pole one

**Internal Trip Release Configuration:**

Series trip single location

**Trip Delay Time In Seconds Per Rated Continuous Current:**

3.000 at 200 pct single location and 8.000 at 200 pct single location

**Inclosure Protection Type For Which Designed:**

Fungus resistant

**Trip Release Ambient Temperature Rating:**

25.0 degrees celsius single location

**Frequency In Hertz:**

60.0 single location

**Terminal Type And Quantity:**

2 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0