NSN 5925-01-133-6626



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-01-133-6626 **Body Style:** Single pole type **Body Length:** 2.000 inches **Body Width:** 0.920 inches **Body Height:** 1.770 inches **Case Material: Plastic Boss Height:** 0.250 inches **Pole Quantity: Mounting Facility Type And Quantity:** 2 clip Storage Type: General purpose warehouse **Special Handling Feature:** Magnetic **Maximum Continuous Load Current Rating Per Pole:** 250.0 milliamperes ac single location **Operating Voltage Type And Rating Per Pole In Volts:** 250.0 ac single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 1000.0 ac single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Magnetic-hydraulic single location **Trip Release Characteristic:** Time delay single location **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 single location **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free **Manual Actuator Type And Quantity:** 1 toggle

Trip-reset

Actuator Function:

NSN 5925-01-133-6626

Circuit Breaker - Page 2 of 2

Fiig: A030a0



Actuator Position Designation:
At pole one
Internal Trip Release Configuration:
Series trip single location
Trip Delay Time In Seconds Per Rated Continuous Current:
0.050 at 200 pct single location and 0.950 at 200 pct single location
Inclosure Protection Type For Which Designed:
Shock resistant and vibration resistant
Frequency In Hertz:
50.0 single location or 60.0 single location
Terminal Type And Quantity:
2 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No