

View Online at <https://aerobasegroup.com/nsn/5925-01-133-7246>

Body Style:

Single pole type

Body Length:

6.000 inches

Body Width:

1.500 inches

Body Height:

3.000 inches

Case Material:

Plastic

Boss Height:

0.125 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

1 terminal

Storage Type:

General purpose warehouse

Maximum Continuous Load Current Rating Per Pole:

25.0 amperes ac single location and 25.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

480.0 ac single location and 250.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

75000.0 ac single location and 5000.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal-magnetic single location

Trip Release Characteristic:

Instantaneous single location and time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

138.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Trip Delay Time In Seconds Per Rated Continuous Current:

30.000 at 200 pct single location and 100.000 at 200 pct single location

Inclosure Protection Type For Which Designed:

Dustproof

Trip Release Ambient Temperature Rating:

40.0 degrees celsius single location

Frequency In Hertz:

60.0 single location

Terminal Type And Quantity:

1 compression and 1 quick disconnect, female

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0