

View Online at <https://aerobasegroup.com/nsn/5925-01-136-6498>

**Body Style:**

Multipole-single actuator type

**Body Length:**

6.000 inches

**Body Width:**

3.000 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

5.125 inches

**Center To Center Distance Between Terminals Parallel To Width:**

1.500 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

4.593 inches

**Switch Contact Arrangement:**

Single pole, double throw

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

1.500 inches

**Fragility Factor:**

Moderately rugged

**Boss Height:**

0.218 inches

**Mounting Surface To Terminal End Distance:**

3.999 inches

**Pole Quantity:**

2

**Mounting Facility Type And Quantity:**

2 threaded hole

**Storage Type:**

General purpose warehouse

**Special Handling Feature:**

Magnetic

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

20.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

240.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

15000.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Thermal-magnetic all locations

**Trip Release Characteristic:**

Instantaneous all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole one

**Auxiliary Switch Function And Quantity:**

2 alarm

**Thread Size:**

0.164 inches

**Switch Location And Position Designation:**

Internal at each pole

**Inclosure Protection Type For Which Designed:**

Fungus proof

**Trip Release Ambient Temperature Rating:**

25.0 degrees celsius all locations

**Switch Terminal Type:**

Wire lead

**Switch Current Rating And Type In Amps:**

20.0 ac

**Switch Voltage Rating And Type In Volts:**

120.0 ac

**Frequency In Hertz:**

60.0 all locations

**Unpackaged Unit Weight:**

0.240 pounds

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

4 quick disconnect, female

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0