

View Online at <https://aerobasegroup.com/nsn/5925-01-136-6503>

**Body Style:**

Multipole-multiple actuator type

**Bushing Length:**

Between 0.203 inches and 0.235 inches

**Body Length:**

Between 5.984 inches and 6.015 inches

**Body Width:**

Between 2.984 inches and 3.016 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

Between 5.109 inches and 5.141 inches

**Center To Center Distance Between Terminals Parallel To Width:**

Between 1.484 inches and 1.516 inches

**Unthreaded Mounting Hole Diameter:**

0.164 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

Between 4.578 inches and 4.610 inches

**Switch Contact Arrangement:**

Single pole, double throw

**Fragility Factor:**

Moderately rugged

**Mounting Surface To Terminal End Distance:**

Between 3.984 inches and 4.016 inches

**Pole Quantity:**

2

**Mounting Facility Type And Quantity:**

2 unthreaded hole

**Storage Type:**

General purpose warehouse

**Maximum Continuous Load Current Rating Per Pole:**

30.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

240.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

15000.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Thermal-magnetic all locations

**Trip Release Characteristic:**

Instantaneous all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole one

**Auxiliary Switch Function And Quantity:**

2 alarm

**Switch Location And Position Designation:**

Internal between pole one and two

**Inclosure Protection Type For Which Designed:**

Fungus proof

**Trip Release Ambient Temperature Rating:**

40.0 degrees celsius all locations

**Switch Terminal Type:**

Wire lead

**Switch Current Rating And Type In Amps:**

15.0 ac and 0.25 dc

**Switch Voltage Rating And Type In Volts:**

240.0 ac and 250.0 dc

**Frequency In Hertz:**

60.0 all locations

**Precious Material And Location:**

Terminal and contact surfaces silver

**Precious Material:**

Silver

**Terminal Type And Quantity:**

4 compression

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0