NSN 5925-01-136-9575

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-136-9575

Body Style: Multipole-single actuator type **Body Length:** 6.000 inches **Body Width:** 4.469 inches **Body Height:** 3.000 inches **Case Material: Plastic Center To Center Distance Between Terminals Parallel To Length:** 5.125 inches **Center To Center Distance Between Terminals Parallel To Width:** 1.500 inches **Unthreaded Mounting Hole Diameter:** 0.190 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 5.125 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.500 inches **Boss Height:** 0.125 inches **Pole Quantity: Mounting Facility Type And Quantity:** 4 unthreaded hole Storage Type: General purpose warehouse **Features Provided:** Adjustable trip release **Maximum Continuous Load Current Rating Per Pole:** 3.0 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:** 600.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 14000.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Magnetic all locations

Time delay all locations

Trip Release Characteristic:

NSN 5925-01-136-9575

Circuit Breaker - Page 2 of 2



Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
125.0 all locations
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Adjustable Trip Setting Current Range Per Pole In Amps:
+8.0/+28.0 ac all locations
Internal Trip Release Configuration:
Series trip all locations
Trip Delay Time In Seconds Per Rated Continuous Current:
35.000 at 200 pct all locations and 65.000 at 200 pct all locations
Frequency In Hertz:
60.0 all locations
Terminal Type And Quantity:
3 clip and 3 compression
Shelf Life:
N/a
Unit Of Measure:
.
Demilitarization:
No
Fiig:
A030a0