

View Online at <https://aerobasegroup.com/nsn/5925-01-137-0159>

Body Style:

Multipole-multiple actuator type

Bushing Length:

Between 0.203 inches and 0.235 inches

Body Length:

Between 5.984 inches and 6.016 inches

Body Width:

Between 2.984 inches and 3.010 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

Between 5.109 inches and 5.141 inches

Center To Center Distance Between Terminals Parallel To Width:

Between 1.484 inches and 1.516 inches

Unthreaded Mounting Hole Diameter:

0.164 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 4.578 inches and 4.610 inches

Switch Contact Arrangement:

Single pole, double throw

Fragility Factor:

Moderately rugged

Mounting Surface To Terminal End Distance:

Between 3.984 inches and 4.016 inches

Pole Quantity:

2

Mounting Facility Type And Quantity:

2 unthreaded hole

Storage Type:

General purpose warehouse

Maximum Continuous Load Current Rating Per Pole:

50.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

15000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic all locations

Trip Release Characteristic:

Instantaneous all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Auxiliary Switch Function And Quantity:

2 alarm

Switch Location And Position Designation:

Internal between pole one and two

Inclosure Protection Type For Which Designed:

Fungus proof

Trip Release Ambient Temperature Rating:

40.0 degrees celsius all locations

Switch Terminal Type:

Wire lead

Switch Current Rating And Type In Amps:

15.0 ac and 0.25 dc

Switch Voltage Rating And Type In Volts:

240.0 ac and 250.0 dc

Frequency In Hertz:

60.0 all locations

Precious Material And Location:

Terminal and contact surfaces silver

Precious Material:

Silver

Terminal Type And Quantity:

4 compression

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0