NSN 5925-01-137-1332

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-137-1332

Body Style:

Multipole-multiple actuator type

Body Length:

2.500 inches

Body Width:

2.250 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

1.938 inches

Center To Center Distance Between Terminals Parallel To Width:

0.750 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.062 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.750 inches

Fragility Factor:

Moderately rugged

Boss Height:

0.140 inches

Mounting Surface To Terminal End Distance:

2.611 inches

Pole Quantity:

3

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

6 threaded hole

Storage Type:

General purpose warehouse

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

15.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

125.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

2000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic-hydraulic all locations

NSN 5925-01-137-1332

Circuit Breaker - Page 2 of 2



Trip Release Characteristic: Time delay all locations Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: 150.0 all locations **Reset Method:** Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

3 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At each pole

External Actuator Linkage Arrangement:

One, two, and three linked

Internal Trip Release Configuration:

Series trip all locations

Thread Size: 0.138 inches

Trip Delay Time In Seconds Per Rated Continuous Current: 0.290 at 200 pct all locations and 1.000 at 200 pct all locations **Inclosure Protection Type For Which Designed:** Dustproof **Frequency In Hertz:** 50.0 all locations or 60.0 all locations **Thread Series Designator:** Unc **Terminal Type And Quantity:** 6 threaded stud Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig:

A030a0