## NSN 5925-01-137-4953

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-137-4953 **Body Style:** Single pole type **Body Length:** 2.000 inches **Body Width:** 0.750 inches **Case Material:** Plastic **Center To Center Distance Between Terminals Parallel To Length:** 1.550 inches **Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:** 1.660 inches **Boss Height:** 0.130 inches **Mounting Surface To Terminal End Distance:** 1.980 inches **Pole Quantity:** 1 **Mounting Facility Type And Quantity:** 2 threaded hole Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 **Maximum Continuous Load Current Rating Per Pole:** 20.0 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 65.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 1000.0 dc single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Magnetic single location **Trip Release Characteristic:** Instantaneous single location **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 single location **Reset Method:** 

Manual **Main Contact Tripping Mechanism Type:** Trip free

## NSN 5925-01-137-4953

Circuit Breaker - Page 2 of 2



Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole one
Internal Trip Release Configuration:
Shunt trip single location
Thread Size:
0.138 inches
Inclosure Protection Type For Which Designed:
General purpose
Thread Series Designator:
Unc
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0