

View Online at <https://aerobasegroup.com/nsn/5925-01-138-1069>

Body Length:

Between 2.418 inches and 2.482 inches

Body Width:

Between 1.718 inches and 1.782 inches

Body Height:

Between 1.811 inches and 1.875 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Width:

Between 0.923 inches and 0.987 inches

Fragility Factor:

Moderately rugged

Boss Height:

Between 0.093 inches and 0.157 inches

Pole Quantity:

2

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

4 clip

Storage Type:

General purpose warehouse

Maximum Continuous Load Current Rating Per Pole:

15.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic-hydraulic all locations

Auxiliary Trip Coil Voltage Type And Rating In Volts:

220.0 ac first location

Trip Release Characteristic:

Instantaneous all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

2 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At each pole

External Actuator Linkage Arrangement:

One and two linked

Internal Trip Release Configuration:

Series trip w/remote trip feature first location

Trip Release Duty Cycle:

Continuous first location

Inclosure Protection Type For Which Designed:

Dustproof

Frequency In Hertz:

60.0 all locations

Terminal Type And Quantity:

5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0